

TECHNICAL CHARACTERISTICS

URANIA FE

PRODUCT CODE: 1347

APPLICATION

Synthetic multigrade motor oil for turbocharged and aspirated Diesel engines of commercial vehicles. It permits reduction of fuel consumption, long drain intervals up to the highest mileages recommended by OEM's on the new generation engines.

SPECIFICATIONS

SAE 5W-30, IVECO 18-1804 CLASSE TFE, CONTRACTUAL TECHNICAL REF. N°I023.M01, ACEA E4/E7, API CF, DAF HP1/HP2, MACK EO-M Plus, MAN M3277, MB-Approval 228.5, MTU OIL TYPE 3, RENAULT VI RXD Performance, SCANIA LDF, VOLVO VDS-3

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	B. & C.
DENSITY 15°C	ASTM D4052	g/cm ³	0,860
VISCOSITY @ 100°C	ASTM D445	cSt	11,4
VISCOSITY INDEX	ASTM D 2270	--	165
FLASH POINT CI. O. C.	ASTM D 92	°C	220
T.B.N.	ASTM D 2896	mg KOH/g	16
POUR POINT	ASTM D 97	°C	-55
FOAM @ 24°C	ASTM D 892	cc/s	0
ACIDITY NUMBER	ASTM D 974	mg KOH/g	2.1

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

03/2014